











No.	Specification	Unit	Value
1	Flange-type	-	√
2	Continuous Torque	Nm	0.06
3	Peak Torque	Nm	0.24
4	Rated Speed	Rpm	60
5	Maximum Speed	Rpm	80
6	Continuous Current	Arms	0.9
7	Peak Current	Arms	3.6
8	Torque Constant	Nm/Arms	0.067
9	Back EMF Constant*	Vrms/rad/s	0.28
10	Resistance Phase to Phase at 25°C	Ω	7.2
11	Inductance Phase to Phase at 25°C	mH	1.5
12	Number of poles	-	12
13	Rotor Inertia	$kg{\cdot}m^2$	0.00011
14	Incremental encoder resolution	ppr	2030320
15	Absolute encoder resolution	ppr	-
16	Absolute Position Accuracy	arcsec	-
17	Repeat Position Accuracy	arcsec	±2
18	Axial Load	N	200
19	Radial Load	Nm	5
20	Axial Run Out*2	um	-
21	Radial Run Out*3	um	-
22	Mass	kg	0.55
23	IP level	-	40
24	Motor Color	-	black
25	Max. DC BUS	V	220

*1 The back electromotive force (back EMF) is the value measured between any two conductors when the motor is running at a constant speed.
*2 *3 Please contact sales.

NOTE:
1.Please make sure the flatness of customer's surface when mounting the motor must be within 0.01/300 mm.
2.The mounting surface without black oxidation.

Wiring Definition	Installation Instructions	Maintenance Instructions

ITEM	DATE	MODIFIED	DESCRIPTION	APPD

TKOOLLE MOTION CONTROL	SCALE	1:X	UNIT	mm		Model	TDI-065022		
						Desc	Rotary Motor		
	GENERAL TOLERANCE					Surface	Black oxidation	DRN	Tang
	Up to	6	30	120	300	600	DWG.NO	M065A006	CHK	Zhou
	±0.1	±0.2	±0.3	±0.4	±0.5		Sheet	1-1	APPD	Le
TKOOLLE MOTION CONTROL INTERNATIONAL CO.,LIMITED							DATE	17-Jul-25		