








No.	Specification	Unit	Value
1	Flange-type	-	-
2	Continuous Torque	Nm	35
3	Peak Torque	Nm	104
4	Rated Speed	Rpm	150
5	Maximum Speed	Rpm	200
6	Continuous Current	Arms	2.8
7	Peak Current	Arms	8.4
8	Torque Constant	Nm/Arms	12.5
9	Back EMF Constant*	Vrms/rad/s	7.4
10	Resistance Phase to Phase at 25°C	Ω	18.1
11	Inductance Phase to Phase at 25°C	mH	37.5
12	Number of poles	-	22
13	Rotor Inertia	$kg{\cdot}m^2$	0.0244
14	Incremental encoder resolution	ppr	1800000
15	Absolute encoder resolution	ppr	24 bit (16777216)
16	Absolute Position Accuracy	arcsec	±15
17	Repeat Position Accuracy	arcsec	±2
18	Axial Load	N	16000
19	Radial Load	Nm	130
20	Axial Run Out*2	um	5/3
21	Radial Run Out*3	um	5/3
22	Mass	kg	12.4
23	IP level	-	40
24	Motor Color	-	black
25	Max. DC BUS	V	220

*1 The back electromotive force (back EMF) is the value measured between any two conductors when the motor is running at a constant speed.
*2 *3 Please contact sales.

NOTE:
1.Please make sure the flatness of customer's surface when mounting the motor must be within 0.01/300 mm.
2.The mounting surface without black oxidation.

Wiring Definition	Installation Instructions	Maintenance Instructions

ITEM	DATE	MODIFIED	DESCRIPTION	APPD

TKOOLLE MOTION CONTROL	SCALE	1:X	UNIT	mm			Model	TDE-160143-P		
							Desc	Rotary Motor		
	GENERAL TOLERANCE						Surface	Black oxidation	DRN	Tang
	Up to	6	6 30	30 120	120 300	300 600	DWG.NO	M160A044	CHK	Zhou
	±0.1		±0.2	±0.3	±0.4	±0.5	Sheet	1-1	APPD	Le
TKOOLLE MOTION CONTROL INTERNATIONAL CO.,LIMITED							DATE	17-Jul-25		