











NOTE:
1.Please make sure the flatness of customer's surface when mounting the motor must be within 0.01/300 mm.
2.The mounting surface without black oxidation.

Wiring Definition	Installation Instructions	Maintenance Instructions

No.	Specification	Unit	Value
1	Flange-type	-	ÿ⁄
2	Continuous Torque	Nm	3.6
3	Peak Torque	Nm	10.8
4	Rated Speed	Rpm	300
5	Maximum Speed	Rpm	350
6	Continuous Current	Arms	1.8
7	Peak Current	Arms	5.4
8	Torque Constant	Nm/Arms	2
9	Back EMF Constant*	Vrms/rad/s	1.2
10	Resistance Phase to Phase at 25°C	Ω	13.1
11	Inductance Phase to Phase at 25°C	mH	29.8
12	Number of poles	-	20
13	Rotor Inertia	$kg{\cdot}m^2$	0.0013
14	Incremental encoder resolution	ppr	3100000
15	Absolute encoder resolution	ppr	24 bit (16777216)
16	Absolute Position Accuracy	arcsec	±15
17	Repeat Position Accuracy	arcsec	±2
18	Axial Load	N	1600
19	Radial Load	Nm	15
20	Axial Run Out*2	um	20/5/3
21	Radial Run Out*3	um	20
22	Mass	kg	2.3
23	IP level	-	40
24	Motor Color	-	black
25	Max. DC BUS	V	220

*1 The back electromotive force (back EMF) is the value measured between any two conductors when the motor is running at a constant speed.
*2 *3 Please contact sales.

ITEM	DATE	MODIFIED	DESCRIPTION	APPD

TKOOLLE MOTION CONTROL

SCALE	UNIT		Model	TDI-120050		
1:X	mm		Desc	Rotary Motor		
GENERAL TOLERANCE			Surface	Black oxidation	DRN	Tang
Up to 6	6 30	30 120	120 300	300 600	DWG.NO	M120A019	CHK	Zhou
±0.1	±0.2	±0.3	±0.4	±0.5	Sheet	1-1	APPD	Le

TKOOLLE MOTION CONTROL INTERNATIONAL CO.,LIMITED DATE 17-Jul-25